

GLASSFLAKE EFFECT SERIES

Moonshine® Russet Ultra Shimmer

Production Code: GFERUSU

Technical Information

Moonshine® effect series are based on our thin borosilicate glass flakes which have an average thickness of 1.0 microns and are coated with high refractive index metal oxides, resulting in unique pigments that display strong interference colours combined with high transparency and extraordinary gloss.

Composition				
Ingredients	Composition	By Weight (%)	CAS No.	CI No.
Calcium Sodium Borosilicate	Glass	65 - 80	65997-17-3	-
Iron Oxide	Fe ₂ O ₃	20 - 35	1309-37-1	77491

Nominal flake thickness (µm):	Uncoated	1.0	Coated	1.21 - 2.21
Particle Size Diameter (µm):	Mean	D10 5	D90 45	(By Malvern Mastersizer 2000S)
Oil Absorption g/100g:	Range	60	100	ASTM D281-12

pH:	7.0 - 11.0	(10% Aqueous Suspension)
Loss on Drying:	0.5 % max	

Trace Elements - Typical:	Mercury (Hg)	2 ppm max	Method C05-1:2009 ICP-MS (Complete Dissolution)
	Arsenic (As)	5 ppm max	
	Lead (Pb)	10 ppm max	
	Cadmium (Cd)	2 ppm max	
	Total Barium (Ba)	50 ppm max	
	Antimony (Sb)	2 ppm max	
	Total Chromium (Cr)	15 ppm max	
	Nickel (Ni)	15 ppm max	
	Copper (Cu)	5 ppm max	
	Cobalt (Co)	5 ppm max	
	Selenium (Se)	2 ppm max	
	Zinc (Zn)*	100 ppm max	
Microorganisms:	100 CFU/g max.		No Pathogens

Glassflake Ltd
Donisthorpe Street Leeds LS10 1PL England info@moonshinepigments.com
www.moonshinepigments.com

This information is given in good faith without guarantee or liability. All values are approximate.